



FEATURE	C110	H510*†	R510*†	R610*†	R710*†	R720
DESCRIPTION	802.11ac Wave 2 dual-concurrent wall plate with built-in DOCSIS 3.0 cable modem	802.11ac Wave 2 dual-concurrent wall switch with five GbE ports and BeamFlex+	Mid-range 802.11ac Wave 2 dual-concurrent AP with MU-MIMO and BeamFlex+	Mid-range 802.11ac Wave 2 dual-concurrent AP with MU-MIMO and BeamFlex+	High-end 802.11ac Wave 2 dual-concurrent AP with MU-MIMO and BeamFlex+	High-end 802.11ac Wave 2 dual-concurrent AP with MU-MIMO, Beamflex+ and 2.5Gbps backhaul
Maximum PHY rate	867 Mbps (5GHz) 300 Mbps (2.4GHz)	867 Mbps (5GHz) 300 Mbps (2.4GHz)	867 Mbps (5GHz), 300 Mbps (2.4GHz)	1300 Mbps (5GHz) 600 Mbps (2.4GHz)	1733 Mbps (5GHz) 800 Mbps (2.4GHz)	1733 Mbps (5GHz) 800 Mbps (2.4GHz)
Wi-Fi technology	802.11ac (5GHz) 802.11n (2.4 GHz)	802.11ac (5GHz) 802.11n (2.4 GHz)	802.11ac (5GHz) 802.11n (2.4GHz)	802.11ac (5GHz) 802.11n (2.4GHz)	802.11ac (5GHz) 802.11n (2.4GHz)	802.11ac (5GHz) 802.11n (2.4GHz)
Concurrent users	100	100	512	512	512	512
Radio chains:streams	2x2:2	2x2:2	2x2:2	3x3:3	4x4:4 SU-MIMO 4x4:3 MU-MIMO	4x4:4 SU-MIMO & MU-MIMO
Antenna patterns (per band)	4	4	64	512	4,000+	4,000+
BeamFlex gains	2dB Tx / 3-5dB Rx	2dB Tx / 3-5dB Rx	up to 4 dB Tx/ 3-5 dB Rx	6dB Tx / 3-5dB Rx	6 dB Tx / 3-5dB Rx	6 dB Tx / 3-5dB Rx
Interference mitigation	up to 5dB	up to 5dB	up to 10dB	up to 15dB	up to 15dB	up to 15dB
PD-MRC	✓	✓	✓	✓	✓	✓
Rx sensitivity (2.4/5GHz)	-96/-95dBm	-99/-96dBm	-103dBm	-100dBm	-104dBm	-104dBm
ChannelFly	✓	✓	✓	✓	✓	✓
Smart meshing	✓	✓	✓	✓	✓	✓
USB	✓	✓	✓	✓	✓	✓
Ethernet ports	2 - 10/100MbE	5 - 1GbE	2 - 1GbE	2 - 1GbE	2 - 1GbE	1 - 1GbE and 1 - 2.5GbE
SKU/Part Number	901-C110-XX00	901-H510-XX00	901-R510-XX00	901-R610-XX00	901-R710-XX00	901-R720-XX00

* Supports Ruckus Unleashed

† Supports Cloud Wi-Fi

PRODUCT GUIDE

ZoneFlex Indoor AP



FEATURE	H500	R300*†	R310*†	R500*†	R600*†	R700†
DESCRIPTION	802.11ac Wave 1 dual-concurrent wall plate with five GbE ports and BeamFlex+	Entry level 802.11n dual-concurrent AP with BeamFlex+	Entry level 802.11ac Wave 1 dual-concurrent AP with BeamFlex+	Mid-range 802.11ac Wave 1 dual-concurrent AP with BeamFlex+	Mid-range 802.11ac Wave 1 dual-concurrent AP with BeamFlex+	High-end 802.11ac Wave 1 dual-concurrent AP with BeamFlex+
Maximum PHY rate	867 Mbps (5GHz) 300 Mbps (2.4GHz)	300 Mbps (5GHz) 300 Mbps (2.4GHz)	867Mbps (5GHz) 300Mbps (2.4GHz)	867 Mbps (5GHz), 300 Mbps (2.4GHz)	1300 Mbps (5GHz) 450 Mbps (2.4GHz)	1300 Mbps (5GHz), 450 Mbps (2.4GHz)
Wi-Fi technology	802.11ac (5GHz) 802.11n (2.4 GHz)	802.11n (2.4 /5GHz)	802.11ac (5GHz) 802.11n (2.4GHz)	802.11ac (5GHz) 802.11n (2.4GHz)	802.11ac (5GHz) 802.11n (2.4 GHz)	802.11ac (5GHz) 802.11n (2.4GHz)
Concurrent users	100	256	100	512	512	512
Radio chains:streams	2x2:2	2x2:2	2x2:2	2x2:2	3x3:3	3x3:3
Antenna patterns (per band)	8	64	64	64	512	3000+
BeamFlex gains	2dB Tx / 3-5dB Rx	4dB Tx	4dB Tx	up to 4 dB Tx/ 3-5 dB Rx	6 dB Tx / 3-5dB Rx	6 dB Tx / 3-5dB Rx
Interference mitigation	up to 5dB	up to 10dB	up to 10dB	up to 10dB	up to 15dB	up to 15dB
PD-MRC	✓	–	–	✓	✓	✓
Rx sensitivity (2.4/5GHz)	-96/-95dBm	-101/-9dBm	-99dB,	-100/-95dBm	-100/-95dBm	-99dBm
ChannelFly	✓	✓	✓	✓	✓	✓
Smart meshing	✓	–	✓	✓	✓	✓
USB	✓	–	–	–	–	–
Ethernet ports	5 - 10/100MbE	1 - 1GbE	2 - 1GbE	2 - 1GbE	2 - 1GbE	2 - 1GbE
SKU/Part Number	901-H500-XX00	901-R300-XX00	901-R500-XX00	901-R500-XX00	901-R600-XX00	901-R700-XX00

* Supports Ruckus Unleashed

† Supports Cloud Wi-Fi



FEATURE	T300*†	T301 Series*†	T610†	T710*†	ZF7781CM	P300
DESCRIPTION	Enterprise class 802.11ac AP with integrated omni or external antennas (5GHz)	Enterprise class 802.11ac AP with 120° or 30° directional integrated antennas	Mid-range 802.11ac Wave 2 dual concurrent AP with BeamFlex+	High-end 802.11ac Wave 2 dual concurrent AP with BeamFlex+	High-end DOCSIS 3.0 802.11n AP	Point-to-Point / Multi-point bridge
Maximum PHY rate	867 Mbps (5GHz) 300 Mbps (2.4GHz)	867 Mbps (5GHz) 300 Mbps (2.4GHz)	1733 Mbps (5GHz), 800 Mbps (2.4GHz)	1733 Mbps (5GHz), 800 Mbps (2.4GHz)	450 Mbps (5GHz) 450 Mbps (2.4GHz)	867 Mbps (5GHz)
Wi-Fi technology	802.11ac (5GHz), 802.11n (2.4GHz)	802.11ac (5GHz), 802.11n (2.4GHz)	802.11ac (5GHz), 802.11n (2.4GHz)	802.11ac (5GHz), 802.11n (2.4GHz)	802.11n (2.4/5GHz)	802.11ac (5GHz)
Concurrent users	512	512	512	512	500	—
Radio chains:streams	2x2:2	2x2:2	4x4:4	4x4:4	3x3:3	2x2:2
Antenna patterns (per band)	64	8	4,000+	4,000+	2000+	—
BeamFlex gains	4dB Tx/ 3-4dB Rx	4dB Tx / 3-4dB Rx	up to 6 dB Tx/ 3-5 dB Rx	up to 6 dB Tx/ 3-5 dB Rx	6dB Tx / 3-4dB Rx	—
Interference mitigation	up to 10dB	up to 10dB	up to 15dB	up to 15dB	up to 15dB	—
PD-MRC	✓	✓	✓	✓	✓	✓
Rx sensitivity (2.4/5GHz)	-100/-95dBm	-100/-94dBm	-104dBm	-104/-104dBm	-101/-96dBm	-96dBm
ChannelFly	✓	✓	✓	✓	✓	✓
Smart meshing	✓	✓	✓	✓	✓	—
Ethernet interface	1 - 1GbE	1 - 1GbE	2 - 1GbE	2 - 1GbE	1 - 1GbE	1 - 1GbES
Fiber interface	—	—	—	✓	—	—
SKU/Part Number	901-T300-XX01 or XX81 for E	901-T301-XX61 for N or -XX51 for S	901-T610-XX01 or XX51 for S	901-T710-XX01 or or XX51 for S	901-7781-XXCM	901-P300-XX01 or -XX02

* Supports Ruckus Unleashed

† Supports Cloud Wi-Fi

Appliance Controller

Controller-Less

Cloud



FEATURE	ZoneDirector 1200	SmartZone 100	SmartZone 300	Unleashed	Cloud Wi-Fi
Number of APs supported	Up to 150	Up to 1,024 / 3,000 cluster	Up to 10,000 / 30,000 cluster	Up to 25	Virtually unlimited number of APs supported
Clients	Up to 4,000	Up to 25,000 / 60,000 cluster	Up to 100,000 / 300,000 per cluster	up to 512	Clients per AP: refer to AP data sheet
Ethernet ports	2 Ethernet ports, auto MDX, autosensing 1GbE	1GE Model: 4 GbE ports	6 x 1GbE ports 4 x 10GbE ports	Refer to selected AP data sheet	N/A
Authentication support	802.1X, Local database-Active Directory, RADIUS, LDAP	802.1X, MAC address	802.1x, Local database, Active Directory, RADIUS, LDAP	802/1x, local database, Active Directory, RADIUS, LDAPr	PSK, 802.1x, Active Directory, RADIUS, LDAP, SMS, social login, open
Guest networking/captive portal	✓	✓	✓	✓	✓
DHCP server		External or Assigned	External or Assigned	✓	External or assigned
AP discovery and control	L2 / L3	L2 / L3	L2 / L3	L2	L2
SSID/WLAN support	256	2,048 / 2,048 cluster	6,144 per SZ-300	16	15/Venue
Management Interface	Web GUI, FlexMaster	Web GUI, CLI	Web GUI, CLI	Web GUI, CLI	Web GUI
Remote Management	No	Yes	Yes	No	Yes
Management protocol(s)	SNMP v3	SNMP v3, RESTful JSON	SNMP v3, RESTful JSON	SNMP v3	N/A
VLAN support	Dynamic VLANs	Dynamic VLANs	Dynamic VLANs	No	Dynamic VLANs
Data Plane	Tunneling or local breakout	Tunneling or local breakout	Tunneling or local breakout	Local Breakout	Tunneled and Local Breakout
Power supply	DC or AC	DC or AC	DC or AC	PoE	APs powered using PoE or optional power supply
Fans	—	Redundant	Six redundant, field swappable fans in three sets	N/A	N/A
SKU/Partnumber	901-1205-XX00	1GE: P01-S104-XX00 10GE: P01-S124-XX00 AP Lic: L09-0001-SG00	901-S300-WW10/00	Refer to Unleashed data sheet for supported APs	Refer to Cloud Wi-Fi data sheet for supported APs

Virtual Controller



FEATURE	Virtual SmartZone-E	Virtual SmartZone-H
Number of APs supported	1,024, 3K w/cluster	10K, 30K w/cluster
Clients	25K / 60K per cluster	100K / 300K per cluster
Ethernet ports	1 vNIC	1 or 3 vNIC
Authentication support	802.1x, Local database, Active Directory, RADIUS, LDAP	802.1x, Local database, Active Directory, RADIUS, LDAP
Guest networking/captive portal	✓	✓
DHCP server	External or vSZ-D assigned	External or vSZ-D assigned
AP discovery and control	L2 / L3	L2 / L3
SSID/WLAN support	2,048	6,000
Management Interface	Web GUI, CLI	Web GUI, CLI
Remote Management	Yes	Yes
Management protocol(s)	SNMP v3	SNMP v3
VLAN support	Dynamic VLANs	Dynamic VLANs
Deployment	Tunneling or local breakout	Tunneling or local breakout
Power supply	N/A	N/A
Fans	N/A	N/A
SKU/Partnumber	L09-VSCG-WW00	L09-VSCG-WW00

SmartZone









FEATURE	vSZ-D
Secured data plane tunneling	Enables forwarding of user data traffic through secure tunnels on Ruckus APs when managed by Virtual SmartZone controllers.
Multiple hypervisor support	Supports the most widely deployed VMware and KVM hypervisors
NFV flexible architecture	Complete separation of Control+Management plane (vSZ) and data plane functions (vSZ-D) via separate VMs that support distributed and centralized deployments providing compelling architecture flexibility
Works seamlessly with virtual Smart Zone	vSZ acts as the controller VM for Ruckus APs as well as vSZ-D (Virtual Data plane) instances providing seamless configuration and management capabilities.
Up to 10 vSZ-D per vSZ and Up to 40 vSZ-D per cluster	The vSZ controller runs in Active/Active (3+1) mode for extremely high availability. Each vSZ-D runs as an independent virtual machine instance that is managed by the vSZ controller.
vSZ Zone affinity for vSZ-DA	This feature enables Ruckus APs in a particular zone establish tunnels with the vSZ-D in that particular zone. Provides flexibility for distributed and managed services deployments where the vSZ-Ds can be co-located on-premise with Ruckus APs (vSZ Zones) on medium/large high density sites that need tunneling. With upto 40 vSZ-Ds per cluster, the SZ 3.5 release can potentially support a large number of such distributed deployments.
DHCP server and NAT	This feature enables a high scale DHCP Server on the vSZ-D. The DHCP Server is a high-scale server specifically designed and architected for Wi-Fi deployments that provide near-real time IP address assignment combined with NAT this provides tremendous value to the operator since it avoids mac-address scaling limits and high costs on the network infrastructure (switches).
Legal Intercept	This feature is useful from a Legal Intercept requirements perspective and enables the ability to mirror packets in both uplink and downlink directions for Wi-Fi clients that have a CALEA warrant.
Support for northbound tunnels L2oGRE	This feature enables vSZ-D to forward WiFi client traffic to a specified 3rd party WAG (Wireless Access Gateway) over L2oGRE protocol standard.
IPv6 support	Supports IPv6 addressing for the vSZ-D interfaces as well as support forwarding of IPv6 client traffic
L3 Roaming (inter vSZ-D tunnels)	This feature enables L3 Roaming when traffic is tunneled to the vSZ-D. The feature relies on inter vSZ-D flexi-vpn tunnels that are dynamically created with minimal user intervention. L3 Roaming can be enabled based on VLANs or subnets.

PRODUCT GUIDE

Ruckus ICX Switches









FEATURE	Access				Access / Aggregation	Aggregation / Core
	ICX 7150-Compact	ICX 7150	ICX 7150 Z-Series	ICX 7250	ICX 7450	ICX 7750
Switch Model						
Switching Capacity (max)	68Gbps	180Gps	304Gbps	256Gbps	336Gbps	2.56Tbps
1GbE RJ-45 ports	12 +2	24 or 48 +2	48	24 or 48	24, 32, or 48	48
1GbE SFP ports	2	4	8	8	48	48
1/2.5GbE RF-45 ports			16		8	
10GbE SFP+ ports (max)	2	4	8	8	12	96
10GbE RJ-45 ports (max)					12	48
40GbE QSFP+ ports (max)					3	32
PoE Power Budget (max)	124W	740W	1480W	1480W	1496W	
Switches per stack (max)	12 ¹	12 ¹	12 ¹	12	12	12
Aggregate stack bandwidth	240Gbps	480Gbps	480Gbps	480Gbps	960Gbps	5.76Tbps

¹ Support for Stacking, Layer 3, OpenFlow and Ruckus Campus Fabric on the ICX 7150 switch family to be offered in a future software release

PRODUCT GUIDE

Ruckus ICX Switches







FEATURE	Access				Access / Aggregation	Aggregation / Core
	ICX 7150-Compact	ICX 7150	ICX 7150 Z-Series	ICX 7250	ICX 7450	ICX 7750
Switch Model						
PoE/PoE+	✓	✓	✓	✓	✓	
Long-Distance Stacking	✓ ¹	✓ ¹	✓ ¹	✓	✓	✓
sFlow	✓	✓	✓	✓	✓	✓
Layer 3 (STATIC, RIP, OSPF)	✓ ¹	✓ ¹	✓ ¹	✓	✓	✓
OpenFlow with Hybrid Port Mode	✓ ¹	✓ ¹	✓ ¹	✓	✓	✓
Ruckus Campus Fabric	✓ ¹	✓ ¹	✓ ¹	✓	✓	✓
Redundant Power Option			✓	✓	✓	✓
Hot Swap Internal power supplies and fans			✓		✓	✓
EEE (Energy Efficient Ethernet)				✓	✓	
VRF				✓	✓	✓
IPsec VPN (with service module)					✓	
MACsec					✓	
BGP					✓	✓
PoH (95W PoE power per port)					✓	
Reversible airflow option					✓	✓
Multi Chassis Trunking (MCT)						✓

¹ Support for Stacking, Layer 3, OpenFlow and Ruckus Campus Fabric on the ICX 7150 switch family to be offered in a future software release

PRODUCT GUIDE

Ruckus Software, Analytics, and Location Solutions



SOFTWARE	
Smart Positioning Technology SPoT (LBS)	 <p>The Ruckus Location-Based Services (LBS) solution enables retailers, stadiums, and transportation hubs to enhance the way they interact with customers based on precise location. Deployed on top of Ruckus Smart Wi-Fi, the Ruckus LBS Solution does not require any additional hardware and has unlimited scalability in the cloud. Send real-time travel updates, targeted promotions, and even classroom notes through footfall traffic and proximity analytics to enrich customer relationships.</p>
Cloudpath (Enrollment)	 <p>Cloudpath Enrollment System (ES) software is a security and policy management platform that enables any IT organization to protect the network by easily and definitively securing users and their wired and wireless devices—while freeing those users and IT itself from the tyranny of passwords. Available cloud-managed or as a virtual instance and priced per user.</p>
SmartCell Insight (SCI) Network Analytics	 <p>SmartCell Insight (SCI) lets you keep on top of a wide range of Key Performance Indicators (KPIs) associated with tens or hundreds of terabytes of data traffic that cross your network every day. Designed with large-scale service provider and enterprise networks in mind, SCI enables IT to extract insight from the network. That insight leads to better informed business and operational decisions.</p>
Network Advisor	 <p>Brocade Network Advisor simplifies storage network management and helps organizations proactively diagnose and troubleshoot issues to maximize uptime, increase operational efficiency, and reduce costs. Customizable, browser-accessible dashboards present data from discovered devices.</p>

Copyright © 2017, Ruckus Wireless, Inc. All rights reserved. Ruckus Wireless and Ruckus Wireless design are registered in the U.S. Patent and Trademark Office. Ruckus Wireless, the Ruckus Wireless logo, BeamFlex+, MediaFlex, FlexMaster, ZoneDirector, SpeedFlex, SmartCast, SmartCell, ChannelFly and Dynamic PSK are trademarks of Ruckus Wireless, Inc. in the United States and other countries. All other trademarks mentioned in this document or website are the property of their respective owners. 17-06-B

Ruckus Wireless, Inc. | 350 West Java Drive | Sunnyvale, CA 94089 USA | T: (650) 265-4200 | F: (408) 738-2065
ruckuswireless.com

